

View Online at <https://aerobasegroup.com/nsn/5320-01-572-3905>

**Fastener Length:**

0.294 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.155 inches and 0.160 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.285 inches and 0.286 inches

**Expansion Device:**

Serrated stem-type w

**End Application:**

Aircraft applications

**Grip Length:**

Between 0.062 inches and 0.141 inches

**Countersink Angle:**

100.0 degrees

**Product Name:**

Blind rivet flush head

**Special Features:**

Rivet-blind; 100deg flush head (ms20426 head), mechanically locked spindle; max length 0.43in

**Material:**

Aluminum alloy 7075 mandrel

**Material Specification:**

Qq-a-430 federal specification single material response mandrel

**Surface Treatment:**

Anodize mandrel

**Surface Treatment Specification:**

Mil-a-8625 yellow military specification 1st treatment response mandrel or mil-c-5541 chem film military specification 2nd treatment response mandrel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.