# NSN 5320-01-572-3905

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-572-3905

# Fastener Length:

0.294 inches

# Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

# Shank Diameter:

Between 0.155 inches and 0.160 inches

## Shank Style:

Self-plugging mechanically locked stem

## Head Major Diameter:

Between 0.285 inches and 0.286 inches

## Expansion Device:

Serrated stem-type w

## End Application:

Aircraft applications

#### Grip Length:

Between 0.062 inches and 0.141 inches

## **Countersink Angle:**

100.0 degrees

## Product Name:

Blind rivet flush head

# Special Features:

Rivet-blind; 100deg flush head (ms20426 head), mechanically locked spindle; max length 0.43in

# Material:

Aluminum alloy 7075 mandrel

# Material Specification:

Qq-a-430 federal specification single material response mandrel

#### Surface Treatment:

Anodize mandrel

# Surface Treatment Specification:

Mil-a-8625 yellow military specification 1st treatment response mandrel or mil-c-5541 chem film military specification 2nd treatment response mandrel

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A040a0

#### Mil-std (military Standard):

Mil-a-8625 spec.