

View Online at <https://aerobasegroup.com/nsn/5320-01-572-3922>

Fastener Length:

0.658 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.155 inches and 0.160 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.285 inches and 0.286 inches

Expansion Device:

Serrated stem-type w

End Application:

Aircraft applications

Grip Length:

Between 0.422 inches and 0.616 inches

Countersink Angle:

100.0 degrees

Product Name:

Blind rivet flush head

Special Features:

Rivet-blind, 100deg flush head (ms20426 head), mechanically locked spindle; max length 1.13in

Material:

Aluminum alloy 7075 mandrel

Material Specification:

Qq-a-430 federal specification single material response mandrel

Surface Treatment:

Anodize mandrel

Surface Treatment Specification:

Mil-a-8625 yellow military specification 1st treatment response mandrel or mil-c-5541 chem film military specification 2nd treatment response mandrel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.