NSN 5320-01-572-3922



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-572-3922 Fastener Length: 0.658 inches **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.155 inches and 0.160 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** Between 0.285 inches and 0.286 inches **Expansion Device:** Serrated stem-type w **End Application:** Aircraft applications **Grip Length:** Between 0.422 inches and 0.616 inches **Countersink Angle:** 100.0 degrees **Product Name:** Blind rivet flush head **Special Features:** Rivet-blind, 100deg flush head (ms20426 head), mechanically locked spindle; max length 1.13in Material: Aluminum alloy 7075 mandrel **Material Specification:** Qq-a-430 federal specification single material response mandrel **Surface Treatment:** Anodize mandrel **Surface Treatment Specification:** Mil-a-8625 yellow military specification 1st treatment response mandrel or mil-c-5541 chem film military specification 2nd treatment response mandrel Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.