NSN 5320-01-573-1128

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-573-1128 **Thread Direction:** Right-hand **Fastener Length:** 24.6 millimeters **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 1.6 millimeters and 1.9 millimeters Width Between Flats: 2.0 millimeters **Shank Diameter:** 4.9 millimeters **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 7.7 millimeters and 8.1 millimeters **Grip Length:** 17.0 millimeters **Thread Size:** 4.0 millimeters **Thread Pitch In Millimeters:** 0.80 **Countersink Angle:** 45.0 degrees **Thread Tolerance Class:** 4h external Material: Titanium alloy **Material Specification:** Ams 4971 6al-6v-2sn assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Hi-shear spec. 294 mfr ref single treatment response **Thread Series Designator:** Iso m Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5320-01-573-1128

Pin-rivet - Page 2 of 2



Fiig:

A528u0