

View Online at <https://aerobasegroup.com/nsn/5320-01-574-3532>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.125 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.104 inches and 0.112 inches

**Shank Diameter:**

Between 0.3215 inches and 0.3220 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.472 inches and 0.502 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

C-17a aircraft

**Grip Length:**

0.625 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.3125 inches

**Product Name:**

Pin-rivet threaded

**Special Features:**

Head centered indented point 0.05 in. Min 0.06 in. Maximum diameter and 0.01 min 0.03 maximum depth

**Material:**

Titanium alloy

**Material Specification:**

Ams4967 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Dps 4.50-197 (hi-kote 1 only) mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0