NSN 5320-01-574-7099

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-574-7099 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 0.450 inches **Head Style:** Straight pan **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.104 inches and 0.119 inches **Shank Diameter:** Between 0.217 inches and 0.219 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.370 inches and 0.390 inches **End Application:** E3a aircraft **Grip Length:** 0.125 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 95000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 7100 double pounds per square inch Material: Steel comp 8740 **Material Specification:** Ams-s-6049 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams-qq-p-416 type ii.Class 2 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5320-01-574-7099

Pin-rivet - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A528u0