

View Online at <https://aerobasegroup.com/nsn/5320-01-574-7099>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

0.450 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.064 inches and 0.074 inches

**Width Between Flats:**

Between 0.104 inches and 0.119 inches

**Shank Diameter:**

Between 0.217 inches and 0.219 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.370 inches and 0.390 inches

**End Application:**

E3a aircraft

**Grip Length:**

0.125 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

95000 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

7100 double pounds per square inch

**Material:**

Steel comp 8740

**Material Specification:**

Ams-s-6049 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams-qq-p-416 type ii.Class 2 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A528u0