NSN 5320-01-576-2053

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-576-2053

| View Online at https://aerobasegroup.com/nsn/5320-01-576 |
|--|
| Fastener Length: |
| Between 2.990 inches and 3.010 inches |
| Head Style: |
| Undersized oval countersunk |
| Head Height: |
| Between 0.003 inches and 0.006 inches |
| Shank Diameter: |
| Between 0.186 inches and 0.189 inches |
| Shank Style: |
| Straight |
| Head Major Diameter: |
| Between 0.297 inches and 0.302 inches |
| Head Minor Diameter: |
| 0.198 mils and 0.208 centimeters |
| Countersink Height: |
| 0.150 inches |
| End Application: |
| F-15sg platform |
| Product Name: |
| Rivet, solid, 100 deg. Flush shear head, aluminum alloy |
| Special Features: |
| Finish is dichromate seal, yellow in color |
| Material: |
| Aluminum alloy 2117 |
| Material Specification: |
| Qq-a-430 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625 military specification 1st treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |

Mil-a-8625 spec.