# NSN 5320-01-578-4037

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-578-4037

# Fastener Length:

Between 0.115 inches and 0.135 inches

### Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

# Shank Diameter:

Between 0.186 inches and 0.190 inches

## Shank Style:

Straight w/radius chamfered tip

## Head Major Diameter:

Between 0.349 inches and 0.357 inches

## Grip Length:

Between 0.045 inches and 0.065 inches

## Shear Strength:

37000 single pounds per square inch

### **Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

## Product Name:

Rivet, solid, ctrsnk 100 deg, precision head, aluminum

#### Material:

Aluminum alloy 2024

#### Material Specification:

Qq-a-430 federal specification single material response

#### Surface Treatment:

Anodize

#### Surface Treatment Specification:

Mil-a-8625, typoe 2, class 1 military specification single treatment response

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A040a0

#### Mil-std (military Standard):

Mil-a-8625 spec.