NSN 5320-01-578-4037

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-578-4037

| Fastene | ·L | .er | ıg | th: |
|---------|----|-----|----|-----|
| Rotwoon | Λ | 11 | 5 | in |

Between 0.115 inches and 0.135 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.186 inches and 0.190 inches

Shank Style:

Straight w/radius chamfered tip

Head Major Diameter:

Between 0.349 inches and 0.357 inches

Grip Length:

Between 0.045 inches and 0.065 inches

Shear Strength:

37000 single pounds per square inch

Countersink Angle:

Between 99.5 degrees and 100.5 degrees

Product Name:

Rivet, solid, ctrsnk 100 deg, precision head, aluminum

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-430 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, typoe 2, class 1 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No Fiig:

.

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.