NSN 5320-01-579-5086

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-579-5086 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.232 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.197 inches and 0.217 inches **Shank Diameter:** 0.405 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.586 inches and 0.592 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** C-135 aircraft **Grip Length:** 0.687 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Countersink Angle:** 100.0 degrees Material: Steel comp 8740 **Material Specification:** Mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 type ii, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

Unit Of Measure:

N/a

NSN 5320-01-579-5086

Pin-rivet - Page 2 of 2



em			

Yes - demil/mli

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.