NSN 5320-01-579-8694

Pin-rivet - Page 1 of 2



and cetyl alcohol

View Online at https://aerobasegroup.com/nsn/5320-01-579-8694

	ass:
3a	
Thread Di	rection:
Right-hand	
Head Style	
Straight pa	n
Head Heig	ht:
Between 0	102 inches and 0.112 inches
Hole Diam	eter:
Between 0	160 inches and 0.180 inches
Shank Dia	meter:
Between 0	342 inches and 0.343 inches
Shank Sty	le:
Pin-rivet, s	traight, threaded
Head Majo	r Diameter:
Between 0	490 inches and 0.520 inches
Chamfer L	ength:
0.046 inch	28
Hole Dept	1:
Between 0	150 inches and 0.170 inches
Grip Leng	ih:
Between 0	490 inches and 0.510 inches
Thready Q	ty Per Inch (tpi):
24	
Min. Tensi	le Strength (psi):
95000 pou	nds per square inch
Thread Siz	e:
0.312 inch	25
Product N	ame:
Protruding	tension head alloy steel 1/16 inch grip variation, 1/32 inch oversize
Special Fe	atures:
Socket-hex	: 0.1270 inch , 0.1295 inch ; double shear pounds : 17600; cadium plate per ams-qq-p-416, type ii, class 2, a
tube per hi	sheer spec. 305
Surface T	eatment:
Cadmium	
Thread Se	ries Designator:
Unjf	
Shelf Life:	
N/a	
Unit Of Me	asure:
Demilitaria	ation:

NSN 5320-01-579-8694

Pin-rivet - Page 2 of 2

Fiig: A528u0

