

View Online at <https://aerobasegroup.com/nsn/5320-01-581-5200>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.302 inches and 1.322 inches

Head Style:

Straight pan

Head Height:

Between 0.037 inches and 0.047 inches

Width Between Flats:

Between 0.079 inches and 0.080 inches

Shank Diameter:

Between 0.162 inches and 0.163 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.242 inches and 0.262 inches

Collar Outside Diameter:

Between 0.288 inches and 0.292 inches

Collarheight:

Between 0.427 inches and 0.447 inches

Collar Inside Diameter:

Between 0.166 inches and 0.173 inches

Grip Length:

1.000 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.164 inches

Shear Strength:

95000 single pounds per square inch

Collar Style:

Threaded break off type

Material:

Steel comp 4340

Material Specification:

Ams 6415 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, tyii, cl2 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0