## NSN 5320-01-581-5709

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-581-5709 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.490 inches and 0.510 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.037 inches and 0.047 inches Width Between Flats: Between 0.079 inches and 0.080 inches **Shank Diameter:** Between 0.162 inches and 0.163 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.242 inches and 0.262 inches **Grip Length:** Between 0.183 inches and 0.193 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** Between 90.0 degrees and 100.0 degrees Material: Steel comp 431 **Material Specification:** Ams 5828 assn standard single material response or mil-s-18732 military specification single material response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A528u0

## NSN 5320-01-581-5709

Pin-rivet - Page 2 of 2



Mil-std (military Standard):

Mil-s-18732 spec.