

View Online at <https://aerobasegroup.com/nsn/5320-01-581-9325>

Thread Direction:

Right-hand

Fastener Length:

39.0 millimeters

Head Style:

Countersunk w/reverse chamfer

Head Height:

1.3 millimeters

Width Between Flats:

Between 3.1 millimeters and 3.6 millimeters

Shank Diameter:

6.0 millimeters

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 5.965 millimeters and 5.990 millimeters

End Application:

Future lynx helicopter

Grip Length:

31.0 millimeters

Min. Tensile Strength (psi):

22200 pounds per square inch

Thread Size:

6.0 millimeters

Thread Pitch In Millimeters:

1.00

Shear Strength:

37000 double pounds per square inch

Countersink Angle:

45.0 degrees

Thread Tolerance Class:

4h external

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams5967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Spec 294 mfr ref single treatment response

Thread Series Designator:

Iso m

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0