

View Online at <https://aerobasegroup.com/nsn/5320-01-581-9325>

**Thread Direction:**

Right-hand

**Fastener Length:**

39.0 millimeters

**Head Style:**

Countersunk w/reverse chamfer

**Head Height:**

1.3 millimeters

**Width Between Flats:**

Between 3.1 millimeters and 3.6 millimeters

**Shank Diameter:**

6.0 millimeters

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 5.965 millimeters and 5.990 millimeters

**End Application:**

Future lynx helicopter

**Grip Length:**

31.0 millimeters

**Min. Tensile Strength (psi):**

22200 pounds per square inch

**Thread Size:**

6.0 millimeters

**Thread Pitch In Millimeters:**

1.00

**Shear Strength:**

37000 double pounds per square inch

**Countersink Angle:**

45.0 degrees

**Thread Tolerance Class:**

4h external

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4928 assn standard single material response or ams5967 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Spec 294 mfr ref single treatment response

**Thread Series Designator:**

Iso m

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0