NSN 5320-01-583-6258

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-583-6258

| ····· • ······ • · ···· · · · · · · · · |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Fastener Length: |
| 1.062 inches |
| Head Style: |
| Straight pan |
| Head Height: |
| Between 0.102 inches and 0.112 inches |
| Width Between Flats: |
| Between 0.160 inches and 0.180 inches |
| Shank Diameter: |
| 0.327 inches |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| Between 0.472 inches and 0.505 inches |
| Lubrication: |
| Cetyl alcohol, specification 305, hi-shear corp |
| End Application: |
| C-135 aircraft |
| Grip Length: |
| 0.562 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Thread Size: |
| 0.312 inches |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams4928 assn standard single material response |
| Surface Treatment: |
| Aluminum |
| Surface Treatment Specification: |
| Per hi-shear specification 294 mfr ref single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5320-01-583-6258

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

