NSN 5320-01-585-2739

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-585-2739

| Fastener Length: |
|--|
| 0.510 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.124 inches and 0.128 inches |
| Shank Style: |
| Self-plugging mechanically locked stem |
| Head Major Diameter: |
| Between 0.221 inches and 0.229 inches |
| Expansion Device: |
| Serrated stem-type w |
| Grip Length: |
| Between 0.188 inches and 0.250 inches |
| Countersink Angle: |
| Between 98.5 degrees and 101.5 degrees |
| Special Features: |
| Partial serrations rivet |
| Material: |
| Nickel alloy 400 locking ring |
| Material Specification: |
| Qq-n-281 federal specification single material response locking ring |
| Surface Treatment: |
| Passivate stem |
| Surface Treatment Specification: |
| Qq-p-416, ty ii, cl 2 federal specification single treatment response sleeve |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| |
| |