# NSN 5320-01-585-3710

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-585-3710



### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.598 inches and 0.638 inches

#### Head Style:

Flush countersunk

### Width Between Flats:

Between 0.094 inches and 0.096 inches

#### Shank Diameter:

Between 0.248 inches and 0.249 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

#### 0.399 inches

Lubrication:

Dry film

# Grip Length:

Between 0.189 inches and 0.250 inches

### Thready Qty Per Inch (tpi):

28

### Thread Size:

0.250 inches

### Shear Strength:

156000 single pounds per square inch

### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

### **Product Name:**

Pin, crimp - 100 degree flush shear head

### Material:

Steel comp h11

### Material Specification:

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

### Thread Series Designator:

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-585-3710

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

