## NSN 5320-01-585-3741

Solid Rivet - Page 1 of 1

A040a0



| View Online at https://aerobasegroup.com/nsn/5320-01-585-3741                               |
|---|
| Fastener Length:  |
| Between 0.240 inches and 0.260 inches   |
| Head Style:   |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)          |
| Shank Diameter:   |
| Between 0.093 inches and 0.097 inches   |
| Shank Style:  |
| Straight  |
| Head Major Diameter:  |
| Between 0.155 inches and 0.190 inches   |
| Shear Strength:   |
| 32000 single pounds per square inch   |
| Countersink Angle:  |
| Between 98.5 degrees and 101.5 degrees  |
| Product Name:   |
| Rivet, solid - 100 degree countersunk head, carbon steel                                    |
| Heat Treatment:   |
| Annealed  |
| Material:   |
| Steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 |
| Material Specification:   |
| 66 federal standard all material responses  |
| Surface Treatment:  |
| Cadmium and chromate  |
| Surface Treatment Specification:  |
| Qq-p-416, type 2, cl 3 federal specification single treatment response                      |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |