## NSN 5320-01-588-5503

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-588-5503

view Offilite at https://defobasegroup.com/nsn/3320-01-300-3303
Fastener Length:
0.605 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.156 inches and 0.160 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
Between 0.282 inches and 0.290 inches
Grip Length:
Between 0.575 inches and 0.605 inches
Countersink Angle:
100.0 degrees
Product Name:
Rivet-blind, 100 degrees flush head, mechanically lockedspindle, bulbed style a, class 2, code m
Special Features:
Sleeve material is monel (nickel-copper alloy)
Material:
Stainless steel locking ring
Material Specification:
Qq-n-281 assn standard single material response sleeve
Surface Treatment:
Passivate locking ring
Surface Treatment Specification:
Ams-qq-p-35 assn standard single treatment response locking ring
Specification Data:
80205-nas9308 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:

A040a0