## NSN 5320-01-588-7707

View Online at https://aerobasegroup.com/nsn/5320-01-588-7707

Pin-rivet - Page 1 of 2

Unjf



**Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.575 inches **Head Style:** Crown countersunk less than 135 degrees **Head Height:** Between 0.0667 inches and 0.0688 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.334 inches and 0.347 inches Lubrication: Cetyl alcohol **End Application:** C-17 aircraft **Grip Length:** 1.250 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1900 inches **Countersink Angle:** 100.0 degrees **Product Name:** Pin-rivet, threaded, 100 degrees fl crown rivet hd Material: Titanium alloy uns r56400 **Material Specification:** Ams4967 federal standard single material response or ams4928 federal standard single material response **Surface Treatment:** Aluminum and chromate **Surface Treatment Specification:** Dps 4.50-197 (hi-kote 1 only) mfr ref single treatment response **Thread Series Designator:** 

## NSN 5320-01-588-7707

Pin-rivet - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0