# NSN 5320-01-590-7121

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-590-7121

## Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

0.642 inches

#### Head Style:

Flush countersunk

## Width Between Flats:

0.104 mils and 0.119 centimeters

## Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.3765 inches and 0.3813 inches

#### Grip Length:

0.317 inches

## Thready Qty Per Inch (tpi):

32

# Thread Size:

0.190 inches

## Shear Strength:

5380 double pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### Material:

Steel comp 4340

#### **Material Specification:**

Ams6515 assn standard single material response or ams6349 assn standard single material response or ams6049 assn standard single material response

#### Surface Treatment:

Cadmium

## Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

#### Thread Series Designator:

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5320-01-590-7121

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

