

View Online at <https://aerobasegroup.com/nsn/5320-01-590-9052>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.170 inches

**Head Style:**

Straight pan

**Width Between Flats:**

0.158 mils and 0.162 centimeters

**Shank Diameter:**

0.406 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

B-1b acft

**Grip Length:**

0.625 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

19100 pounds per square inch

**Thread Size:**

0.375 inches

**Shear Strength:**

32 double pounds per square inch

**Product Name:**

Hi-lok pin, protruding tension head, ph13-8mo stainless steel, 1/16" grip variation, 1/32" oversize

**Material:**

Stainless steel

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Hi-shear specification 262 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0