

View Online at <https://aerobasegroup.com/nsn/5320-01-590-9053>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

1.014 inches

Head Style:

Straight pan

Head Height:

Between 0.130 inches and 0.140 inches

Width Between Flats:

0.158 mils and 0.162 centimeters

Shank Diameter:

0.406 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.585 inches and 0.620 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

B-1b aircraft

Grip Length:

0.469 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

19100 pounds per square inch

Shear Strength:

32400 double pounds per square inch

Product Name:

Hi-lok pin, protuding tension head, ph13-8mo stainless steel, 1/16" grip variation, 1/32" oversize

Material:

Stainless steel

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Hi-shear specification 262 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0