NSN 5320-01-591-1252

Pin-rivet - Page 1 of 2





Thread Class:

3a

Fastener Length:

Between 0.628 inches and 0.648 inches

Head Style:

Straight pan

Head Height:

Between 0.045 inches and 0.055 inches

Width Between Flats:

0.079 mils and 0.081 centimeters

Shank Diameter:

Between 0.201 inches and 0.203 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.206 inches and 0.316 inches

Grip Length:

0.308 mils and 0.318 centimeters

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Product Name:

Hi-lock pin protruding shear head h-11 steel alloy 1/16 in grip variation 1/16 in oversize

Special Features:

Tube has a cetyl alchol finish per hi-shear specification 305; heat treat 132, 000 psi min per ams 6487

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Nickel and cadmium

Surface Treatment Specification:

Ams 2416 assn standard 1st treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-591-1252

Pin-rivet - Page 2 of 2

Fiig: A528u0

