

View Online at <https://aerobasegroup.com/nsn/5320-01-591-2872>

**Thread Class:**

3a

**Fastener Length:**

Between 0.690 inches and 0.710 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.045 inches and 0.055 inches

**Width Between Flats:**

0.079 mils and 0.081 centimeters

**Shank Diameter:**

Between 0.202 inches and 0.203 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.205 inches and 0.316 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

0.375 centimeters

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Shear Strength:**

8600 double pounds per square inch

**Product Name:**

Hi-lok pin protruding shear head

**Material:**

Steel comp h11

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium and nickel

**Surface Treatment Specification:**

Ams 2416 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0