

View Online at <https://aerobasegroup.com/nsn/5320-01-591-4165>

**Thread Class:**

3a

**Fastener Length:**

Between 1.785 inches and 1.805 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.120 inches and 0.140 inches

**Width Between Flats:**

0.158 mils and 0.162 centimeters

**Shank Diameter:**

Between 0.374 inches and 0.375 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.530 inches and 0.600 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

1.250 centimeters

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Shear Strength:**

29200 double pounds per square inch

**Product Name:**

Hi-lok pin protruding tension head

**Material:**

Steel comp h11

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Nickel and cadmium

**Surface Treatment Specification:**

Ams 2416 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0