

View Online at <https://aerobasegroup.com/nsn/5320-01-591-5172>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.687 inches and 1.707 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.150 inches and 0.160 inches

**Width Between Flats:**

0.1895 mils and 0.1930 centimeters

**Shank Diameter:**

Between 0.4677 inches and 0.4682 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.660 inches and 0.695 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

0.870 mils and 0.880 centimeters

**Thread Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

25800 pounds per square inch

**Thread Size:**

0.438 inches

**Shear Strength:**

43100 double pounds per square inch

**Product Name:**

Hi-lok pin protruding tension head ph13-8mo stainless steel 1/16" grip variation, 1/32" oversize

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Hi-shear 262 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0