

View Online at <https://aerobasegroup.com/nsn/5320-01-591-5172>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.687 inches and 1.707 inches

Head Style:

Straight pan

Head Height:

Between 0.150 inches and 0.160 inches

Width Between Flats:

0.1895 mils and 0.1930 centimeters

Shank Diameter:

Between 0.4677 inches and 0.4682 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.660 inches and 0.695 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.870 mils and 0.880 centimeters

Thread Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

25800 pounds per square inch

Thread Size:

0.438 inches

Shear Strength:

43100 double pounds per square inch

Product Name:

Hi-lok pin protruding tension head ph13-8mo stainless steel 1/16" grip variation, 1/32" oversize

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Hi-shear 262 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0