

View Online at <https://aerobasegroup.com/nsn/5320-01-591-5179>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

1.685 inches

Head Style:

Straight pan

Head Height:

Between 0.178 inches and 0.188 inches

Width Between Flats:

0.2207 mils and 0.2242 centimeters

Shank Diameter:

Between 0.5302 inches and 0.5307 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.755 inches and 0.790 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

1.000 inches

Thread Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

34300 pounds per square inch

Thread Size:

0.500 inches

Shear Strength:

55400 double pounds per square inch

Product Name:

Hi-lok pin protruding tension head ph13-8mo stainless steel 1/16" grip variation, 1/32" oversize

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Hi-shear specification 262 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0