

View Online at <https://aerobasegroup.com/nsn/5320-01-591-5221>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

0.920 inches

Head Style:

Straight pan

Head Height:

Between 0.130 inches and 0.140 inches

Width Between Flats:

0.1582 mils and 0.1617 centimeters

Shank Diameter:

Between 0.3896 inches and 0.3901 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.565 inches and 0.600 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

19100 pounds per square inch

Thread Size:

0.375 inches

Shear Strength:

30000 double pounds per square inch

Product Name:

Hi-lok pin protruding tension head ph13-8mo stainless steel 1/16" grip variation, 1/64" oversize

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Hi-shear specification 262 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0