

View Online at <https://aerobasegroup.com/nsn/5320-01-591-5221>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

0.920 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.130 inches and 0.140 inches

**Width Between Flats:**

0.1582 mils and 0.1617 centimeters

**Shank Diameter:**

Between 0.3896 inches and 0.3901 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.565 inches and 0.600 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

19100 pounds per square inch

**Thread Size:**

0.375 inches

**Shear Strength:**

30000 double pounds per square inch

**Product Name:**

Hi-lok pin protruding tension head ph13-8mo stainless steel 1/16" grip variation, 1/64" oversize

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Hi-shear specification 262 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0