NSN 5320-01-591-6828

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-591-6828



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.535 inches and 1.555 inches

Head Style:

Flush countersunk

Width Between Flats:

0.158 mils and 0.162 centimeters

Shank Diameter:

Between 0.389 inches and 0.390 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.555 inches and 0.560 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

1.000 centimeters

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Shear Strength:

31600 double pounds per square inch

Countersink Angle:

100.0 degrees

Product Name:

Hi-lok pin 100 degrees flush shear head 1/64 inch oversize

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium and nickel

Surface Treatment Specification:

Ams 2416 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5320-01-591-6828

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

