NSN 5320-01-591-7011

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-591-7011 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.910 inches and 1.930 inches **Head Style:** Flush countersunk Width Between Flats: 0.158 mils and 0.162 centimeters **Shank Diameter:** Between 0.389 inches and 0.390 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.555 inches and 0.560 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.375 centimeters Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Shear Strength:** 31600 double pounds per square inch **Countersink Angle:** 100.0 degrees **Product Name:** Hi-lok pin 100 degrees flush shear head, 1/64 inch oversize Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and nickel **Surface Treatment Specification:** Ams 2416 assn standard single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

NSN 5320-01-591-7011

Pin-rivet - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A528u0