

NSN 5320-01-591-7131 Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-591-7131 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.178 inches and 1.198 inches **Head Style:** Flush countersunk Width Between Flats: 0.127 mils and 0.130 centimeters **Shank Diameter:** Between 0.327 inches and 0.328 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.469 inches and 0.474 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.688 centimeters Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Shear Strength:** 22300 double pounds per square inch **Countersink Angle:**

100.0 degrees

Product Name:

Hi-lok pin 100 degrees flush shear head 1/64 inch oversize

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium and nickel

Surface Treatment Specification:

Ams 2416 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5320-01-591-7131

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0