NSN 5320-01-591-7132

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-591-7132 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.303 inches and 1.323 inches **Head Style:** Flush countersunk Width Between Flats: 0.127 mils and 0.130 centimeters **Shank Diameter:** Between 0.327 inches and 0.328 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.469 inches and 0.474 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.813 centimeters Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Shear Strength:** 22300 double pounds per square inch **Countersink Angle:** 100.0 degrees **Product Name:** Hi-lok pin 10 0deg flush shear head 1/64 inch oversize Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and nickel **Surface Treatment Specification:** Ams 2416 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5320-01-591-7132

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0