

View Online at <https://aerobasegroup.com/nsn/5320-01-591-8742>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

0.8745 inches

Head Style:

Straight pan

Head Height:

Between 0.055 inches and 0.065 inches

Width Between Flats:

0.0791 mils and 0.0801 centimeters

Shank Diameter:

Between 0.1560 inches and 0.1595 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.306 inches and 0.322 inches

Lubrication:

Cetyl alcohol

Grip Length:

0.562 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Material:

Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5000 military specification single material response or ams6415 assn standard single material response or ams6484 assn standard single material response or mil-s-5625 military specification single material response or ams6382 assn standard single material response or ams6349 assn standard single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.