

View Online at <https://aerobasegroup.com/nsn/5320-01-591-8742>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

0.8745 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.055 inches and 0.065 inches

**Width Between Flats:**

0.0791 mils and 0.0801 centimeters

**Shank Diameter:**

Between 0.1560 inches and 0.1595 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.306 inches and 0.322 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

0.562 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Material:**

Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification single material response or ams6415 assn standard single material response or ams6484 assn standard single material response or mil-s-5625 military specification single material response or ams6382 assn standard single material response or ams6349 assn standard single material response or mil-s-6049 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.