## NSN 5320-01-591-8742

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-591-8742

**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

0.8745 inches

## Head Style:

Straight pan

#### **Head Height:**

Between 0.055 inches and 0.065 inches

## Width Between Flats:

0.0791 mils and 0.0801 centimeters

#### Shank Diameter:

Between 0.1560 inches and 0.1595 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.306 inches and 0.322 inches

#### Lubrication:

Cetyl alcohol

## Grip Length:

0.562 inches

## Thready Qty Per Inch (tpi):

32

## **Thread Size:**

0.164 inches

## Material:

Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740

## Material Specification:

Mil-s-5000 military specification single material response or ams6415 assn standard single material response or ams6484 assn standard single material response or ams6382 assn standard single material response or ams6349 assn standard single material response or ams6349 military specification single material response or ams6349 assn standard single material response or ams6349 assn standard single material response or ams6349 military specification s

## Surface Treatment:

Cadmium

## Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

## **Thread Series Designator:**

Unjc

## Shelf Life:

N/a

#### Unit Of Measure:

---

Demilitarization:

No

# NSN 5320-01-591-8742

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

