NSN 5320-01-591-9111

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-591-9111 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.615 inches and 1.635 inches **Head Style:** Flush countersunk Width Between Flats: 0.127 mils and 0.130 centimeters **Shank Diameter:** Between 0.327 inches and 0.328 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.469 inches and 0.474 inches **Grip Length:** 1.125 centimeters Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Shear Strength:** 22300 double pounds per square inch **Countersink Angle:** 100.0 degrees **Product Name:** Hi-lok pin 100 degrees flush shear head Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and nickel **Surface Treatment Specification:** Ams 2416 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

NSN 5320-01-591-9111

Pin-rivet - Page 2 of 2



_		••	• •					
וו	em	ш	112	r17	2+	\sim	n	
$\boldsymbol{-}$	CIII	••	ıιa	114	.aı	ı		

No

Fiig:

A528u0