

View Online at <https://aerobasegroup.com/nsn/5320-01-592-2038>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.083 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.080 inches and 0.090 inches

**Width Between Flats:**

0.122 mils and 0.142 centimeters

**Shank Diameter:**

Between 0.264 inches and 0.266 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.415 inches and 0.440 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

0.687 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.250 inches

**Shear Strength:**

10490 double pounds per square inch

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4928 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Per hi-shear specification 294 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0