## NSN 5320-01-592-2682

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-592-2682

Fastener Length:
Between 0.428 inches and 0.448 inches
Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:** 

Between 0.1560 inches and 0.1585 inches

**Shank Style:** 

Straight w/radius chamfered tip

**Head Major Diameter:** 

Between 0.268 inches and 0.292 inches

**Countersink Angle:** 

Between 99.0 degrees and 101.0 degrees

**Product Name:** 

Rivet, 100 degrees precision head, close tolerance shank

**Special Features:** 

Supersedes p/n bacr15ba5ad7

**Heat Treatment:** 

T-4 solution heat treated

Material:

Aluminum alloy 2117

**Material Specification:** 

Qq-a-430, 2117-t4 federal specification single material response

**Surface Treatment:** 

Chromate

**Surface Treatment Specification:** 

Mil-c-5541, class 1a, gold/yellow military specification single treatment response

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No Fiig:

1010

A040a0

Mil-std (military Standard):

Mil-c-5541 spec.