# NSN 5320-01-592-2682

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-592-2682

# Fastener Length:

Between 0.428 inches and 0.448 inches

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

# Shank Diameter:

Between 0.1560 inches and 0.1585 inches

# Shank Style:

Straight w/radius chamfered tip

# Head Major Diameter:

Between 0.268 inches and 0.292 inches

# **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

# Product Name:

Rivet, 100 degrees precision head, close tolerance shank

# Special Features:

Supersedes p/n bacr15ba5ad7

#### Heat Treatment:

T-4 solution heat treated

## Material:

Aluminum alloy 2117

## Material Specification:

Qq-a-430, 2117-t4 federal specification single material response

## Surface Treatment:

Chromate

## Surface Treatment Specification:

Mil-c-5541, class 1a, gold/yellow military specification single treatment response

#### Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A040a0

## Mil-std (military Standard):

Mil-c-5541 spec.