

View Online at <https://aerobasegroup.com/nsn/5320-01-593-4814>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

0.687 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.127 inches and 0.129 inches

**Shank Diameter:**

0.500 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.468 inches and 0.473 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corporation and dry film

**Grip Length:**

0.187 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.312 inches

**Countersink Angle:**

100.0 degrees

**Product Name:**

Pin-riquet, threaded, shear, 100 degrees c'sunk head, hex pt drive

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams 2700 method 1 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0