## NSN 5320-01-593-4828

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-593-4828 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 2.770 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.094 inches and 0.096 inches **Shank Diameter:** 0.250 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.358 inches and 0.365 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corporation and dry film **Grip Length:** 2.375 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees **Product Name:** Pin-rivet, threaded, shear, 100 degrees c'sunk head, hex pt drive Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Ams 2700 method 1 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-593-4828

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0