

View Online at <https://aerobasegroup.com/nsn/5320-01-596-1015>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.113 inches and 2.133 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.103 inches and 0.115 inches

**Width Between Flats:**

Between 0.221 inches and 0.224 inches

**Shank Diameter:**

Between 0.488 inches and 0.493 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.735 inches and 0.770 inches

**Lubrication:**

Dry film

**End Application:**

Global hawk

**Grip Length:**

1.438 inches

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.500 inches

**Shear Strength:**

37300 double pounds per square inch

**Product Name:**

Hi-lok pin protruding shear head

**Special Features:**

Lubrication is per mil-I-46010 type 1

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5737 assn standard single material response or asm 5731 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0