# NSN 5320-01-598-2723

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-598-2723

# Fastener Length:

0.467 inches

## Head Style:

Cooper's (included angle - 135 degrees and over)

## Head Height:

Between 0.030 inches and 0.036 inches

## Shank Diameter:

Between 0.124 inches and 0.128 inches

### Shank Style:

Straight w/radius chamfered tip

## Head Major Diameter:

Between 0.260 inches and 0.277 inches

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

## Product Name:

Rivet, flush seal

# Special Features:

Comes with a synthetic rubber o-ring per mil-r-6855, class 1 grade 60 located on the shaft just below the head. O-ring inside diameter 0.116 thickness 0.025.

#### Material:

Aluminum alloy 2117

#### **Material Specification:**

Qq-a-430, 2117-t4 federal specification single material response

#### Surface Treatment:

Chromate

#### Surface Treatment Specification:

Mil-c-5541, class 1a military specification single treatment response

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

#### Fiig:

A040a0

#### Mil-std (military Standard):

Mil-c-5541 spec.