

View Online at <https://aerobasegroup.com/nsn/5320-01-599-4500>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

1.020 inches

Head Style:

Straight pan

Head Height:

Between 0.077 inches and 0.090 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2641 inches and 0.2651 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

Global hawk

Grip Length:

0.625 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Shear Strength:

10490 double pounds per square inch

Product Name:

Hi-lok pin protruding tension head a-286 high temperature alloy

Material:

Iron alloy 660

Material Specification:

Ams 5737 assn standard single material response or ams 5731 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Hi-shear specification 258 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0